

SHOWA

# 377-IP

Fully nitrile dipped with extra nitrile foam coating over polyester/nylon liner reinforced with engineered Anti-impact protection

## FEATURES

- Impermeable full nitrile coating all over the hand.
- Extra nitrile foam coating finish on the palm.
- High-abrasion resistance.
- Anti-impact protection hand sewn with high standards of care in our factory.
- Unique SHOWA ergonomic shape that replicates the natural curve of the human hand.
- High-visibility green colour for visible hand signaling.

## BENEFITS

- Impact protection reduces shock energy on metacarpals and knuckles, adds pinch-point protection for fingertips.
- A flexible, robust glove offering great dexterity combine with good resistance to tearing.
- Foam nitrile palm finish disperses oil, sludge and mud away to maximize grip.
- Nitrile protects from water, oils, hydrocarbons grease splashes with optimal long-lasting grip.
- Excellent fitting due to optimal liner design.
- Seamless knit designed to prevent irritation.
- No latex - minimal allergy risks

## INDUSTRY



Construction



Mechanical



Oil and Gas



Railways



Warehousing & Distribution

## IDEAL APPLICATIONS

- Cementing
- Concreting
- Concrete pouring
- Demolition
- Drainage, piping
- Mortar
- Light assembly of oil-coated pieces
- Deck crew
- Digging
- Drilling
- Pipe Fitters



## MATERIAL

- Nylon
- Polyester
- Seamless knit

## COATING

- Foam nitrile
- Nitrile



## NORMS



# SHOWA 377-IP



## PACKAGING

- 5 Pair per polybag
- 12 Polybags per case
- 60 Pair per case



## SIZES

- M
- L
- XL
- XXL



## COLOUR

- Black/blue



## [ YOU MIGHT ALSO BE INTERESTED IN

### SHOWA 376R



**MATERIAL**  
Nylon  
**COATING**  
Foam nitrile  
**CATEGORY**  
General Purpose

### SHOWA 377



**MATERIAL**  
Nylon  
**COATING**  
Foam nitrile  
**CATEGORY**  
General Purpose

### SHOWA 379



**MATERIAL**  
Cotton  
**COATING**  
Foam nitrile  
**CATEGORY**  
Chemical

### SHOWA 477



**MATERIAL**  
Fixed insulated acrylic  
**COATING**  
Foam nitrile  
**CATEGORY**  
Cold

## [ USER INSTRUCTIONS

Do not use where there are chemical, electrical, thermal or entanglement risks. Wash at 40°C max. Performance levels as per standard EN388 retained after 3 washes, subject to variations linked to actual usage conditions. The performance levels apply to the coated surface only. Store in a dry place, away from the light.

## [ DISCLAIMER

The descriptions, characteristics, applications and photos are given for information purposes and do not constitute a contractual commitment. The manufacturer reserves the right to make any modifications it deems necessary.

## Get in touch

SHOWA International | WTC - Tower I - Strawinsky laan 1817 - 1077 XX Amsterdam - The Netherlands  
showagroup.eu | info@showagroup.eu

© SHOWA Group 2018 | All rights reserved