

SHOWA
890



Unlined viton over butyl coating with longue sleeves

[**FEATURES**

- Unlined Viton® over Butyl
- 0.70mm thick
- 350mm long
- Smooth grip

[**BENEFITS**

- Protection against aromatics such as benzene, toluene, xylene
- Excellent barrier to most chlorinated solvents and aliphatic hydrocarbons

[**INDUSTRY**



Chemical



Oil and Gas



Pharmaceutical



Railways

[**IDEAL APPLICATIONS**

- Chemical spraying & treatment
- Coating preparation
- Laboratory, pharma & analyses
- Painting & spray workshops



MATERIAL

- Unsupported

COATING

- Viton



NORMS



SHOWA 890



PACKAGING

- 12 Pair per polybag
- 1 Polybags per case
- 12 Pair per case



SIZES

- L
- XL



COLOUR

- Black



THICKNESS

- 0.70mm



[YOU MIGHT ALSO BE INTERESTED IN

SHOWA
892



MATERIAL
Unsupported
COATING
Viton
CATEGORY
Chemical

[USER INSTRUCTIONS

Do not use where there are electrical, thermal or entanglement risks. Discard used gloves in compliance with local regulations. Permeation information does not reflect the actual duration of protection in the workplace due to other factors that may influence the performance. Store in a dry place, away from the light.

[DISCLAIMER

The descriptions, characteristics, applications and photos are given for information purposes and do not constitute a contractual commitment. The manufacturer reserves the right to make any modifications it deems necessary.

Get in touch

SHOWA International | WTC - Tower I - Strawinskyaan 1817 - 1077 XX Amsterdam - The Netherlands
showagroup.eu | info@showagroup.eu

© SHOWA Group 2018 | All rights reserved