

SHOWA A0160

Polyurethane fingertips coating over antistatic nylon/acrylic liner

FEATURES

- Coated fingertips
- Elasticated cuff
- Standard finish
- Without special treatment
- Surface resistivity 105 to 107
- Seamless knit



BENEFITS

- A light, elastic low-lint glove, resistant to deformation and with antistatic properties
- Protects extremities from oils and micro-cuts while remaining flexible
- No fingerprints left on handled objects, extremities protected
- Minimal allergy risks
- No irritation by seams in contact with the skin
- Great freedom of movement for the wrist

INDUSTRY



Aerospace



Automotive



Cleanrooms



Electronics



Printing

[IDEAL APPLICATIONS

- Intricate parts handling
- Mechanical and engineering
- Semiconductors
- Cleanroom
- Integrated circuits
- Microelectronic



- Acrylic
- Seamless knit
- Nylon

COATING

Polyurethane



NORMS







4

SHOWA

A0160



PACKAGING

- 10 Pair per polybag
- 24 Polybags per case
- 240 Pair per case



SIZES

- S
 - M
- L
- XL



COLOUR

Grey & white



YOU MIGHT ALSO BE INTERESTED IN

SHOWA A0150



MATERIAL
Acrylic
COATING
Uncoated
CATEGORY
Antistatic

SHOWA **A0170**



MATERIAL
Acrylic
COATING
Polyurethane
CATEGORY
Antistatic

USER INSTRUCTIONS

Protection against mechanica! risks, with electrostatic properties. Do not use where there are chemical, electrical, thermal or entanglement risks. Wash at 40°C max. Performance levels as per standard EN388 retained after 3 washes, subject to variations linked to actual usage conditions. The performance levels apply to the coated surface only. Store in a dry place, away from the light. All clothing and shoes worn with the glove with electrostatic dissipation properties must also be designed taking the electrostatic risk into account.

DISCLAIMER

The descriptions, characteristics, applications and photos are given for information purposes and do not constitute a contractual commitment. The manufacturer reserves the right to make any modifications it deems necessary.

Get in touch