

SHOWA A0170

Polyurethane palm coating over antistatic nylon/acrylic liner

FEATURES

- Coated palm
- Elasticated cuff
- Standard finish
- Without special treatment
- Surface resistivity ON PALM SIDE 106 to 107
- Anatomical shape
- Seamless knit



BENEFITS

- A light, elastic low-lint glove, resistant to deformation and with antistatic properties
- Protects the hand from oils and abrasion while remaining elastic and breathable
- Breathable back of hand to reduce perspiration
- Minimal allergy risks
- Designed for easy movement and continuous wear
- No irritation by seams in contact with the skin
- Great freedom of movement for the wrist

INDUSTRY



Aerospace



Automotive



Cleanrooms



Electronics



Printing

[IDEAL APPLICATIONS

- Intricate parts handling
- Mechanical and engineering
- Semiconductors
- Cleanroom
- Integrated circuits
- Microelectronic



MATERIAL

- Acrylic
- Nvlon
- Seamless knit

COATING

Polyurethane



NORMS







4

SHOWA

A0170



PACKAGING

- 10 Pair per polybag
- 24 Polybags per case
- 240 Pair per case



SIZES

- S
- M
- L
- XI



COLOUR

Grey & white



USER INSTRUCTIONS

Protection against mechanica! risks, with electrostatic properties. Do not use where there are chemical, electrical, thermal or entanglement risks. Wash at 40°C max. Performance levels as per standard EN388 retained after 3 washes, subject to variations linked to actual usage conditions. The performance levels apply to the coated surface only. Store in a dry place, away from the light. All clothing and shoes worn with the glove with electrostatic dissipation properties must also be designed taking the electrostatic risk into account.

DISCLAIMER

The descriptions, characteristics, applications and photos are given for information purposes and do not constitute a contractual commitment. The manufacturer reserves the right to make any modifications it deems necessary.

