

SHOWA

# DURACoil 546



- HPPE
- Polyester

## FEATURES

- 13 gauge seamless knit liner with HPPE
- Foamed polyurethane palm coating for good grip & aeration
- EN 388:2016: Cut Level C
- ANSI/ISEA 105-16: A3
- Lightweight, flexible liner with elastic knitted wrist
- Breathable open back design

## BENEFITS

- Ultra-comfortable multi-purpose glove with durable cut resistant properties for precision handling.
- Increased cut resistance performance due to engineered fibre wrapping technology
- PU foamed coating protects the hand from oils and abrasions while remaining breathable
- Maximum comfort when performing delicate tasks due to soft and flexible HPPE properties combined with high multifilament wrapping technique
- Breathable back of hand to reduce perspiration and keep hands dry
- Ergonomically designed to replicates the natural curves for enhanced dexterity and longer use
- Cost-efficient gloves that can be laundered and re-used
- Seamless knit designed to prevent irritation

## INDUSTRY



Aerospace



Automotive



Engineering



Glass



Manufacturing



Mechanical



Metallurgy



Mining



Railways



Warehousing & Distribution

## IDEAL APPLICATIONS

- Dry & oily parts assembly
- Bottling
- Glass & window fixing
- Canning
- White goods
- Automotive repairs & maintenance
- Mechanical engineering
- Mounting & dismantling
- Electrical Maintenance

## COATING

- Polyurethane



## NORMS



SHOWA

# DURACoil 546



## PACKAGING

- 10 Pair per polybag
- 12 Polybags per case
- 120 Pair per case



## SIZES

- S
- M
- L
- XL
- XXL



## COLOUR

- Grey



## THICKNESS

- 1.3mm



## [ YOU MIGHT ALSO BE INTERESTED IN

SHOWA  
**541**



**MATERIAL**  
HPPE  
**COATING**  
Polyurethane  
**CATEGORY**  
Cut

SHOWA  
**DURACoil 546W**



**MATERIAL**  
Engineered yarn  
**COATING**  
Polyurethane  
**CATEGORY**  
Cut

SHOWA  
**DURACoil 546X**



**MATERIAL**  
Engineered yarn  
**COATING**  
Uncoated  
**CATEGORY**  
Cut

## [ USER INSTRUCTIONS

Do not use where there are chemical, electrical, thermal or entanglement risks. Wash at 40°C max. Performance levels as per standard EN388 retained after 3 washes, subject to variations linked to actual usage conditions. The performance levels apply to the coated surface only. Store in a dry place, away from the light.

## [ DISCLAIMER

The descriptions, characteristics, applications and photos are given for information purposes and do not constitute a contractual commitment. The manufacturer reserves the right to make any modifications it deems necessary.

## Get in touch

SHOWA International | WTC - Tower I - Strawinskyaan 1817 - 1077 XX Amsterdam - The Netherlands  
showagroup.eu | info@showagroup.eu

© SHOWA Group 2018 | All rights reserved