

SHOWA

# S-TEX 377

Double-dipped, fully coated, with an extra foamed nitrile finish on palm over 13 Gauge knitted liner

## FEATURES

- Engineered Hagane Coil® technology
- EN388:2016 Cut resistance level 4 / D (19Newton)
- Double-dipped, fully coated, with an extra foamed nitrile finish on palm
- 13 Gauge knitted liner.
- Anatomical hand shape design
- Seamless knit
- Nitrile foam grip

## BENEFITS

- Excellent cut resistance performance: D/19 Newton
- Nitrile coating with a second foamed nitrile coating providing high abrasion resistance EN388: 4
- Protects the hand from oils, hydrocarbons, grease and abrasion, with long lasting grip performance under wet and oily conditions
- An ergonomically designed hand mould replicates the natural curvature of the human hand and thus reduces hand fatigue, increasing productivity and dexterity
- Seamless knitting gives no irritation
- Liquid-proof to end of coated area

## INDUSTRY



Aerospace



Agriculture



Construction



Engineering



Glass



Manufacturing



Mechanical



Mining

## IDEAL APPLICATIONS

- Glass & window fixing
- Glass & window handling
- Plumbing
- Steel erecting
- Steel fixing
- Washing & cleaning
- Dry & oily parts assembly
- Heavy equipment handling
- Bottling
- Canning
- Automotive repairs & maintenance
- Light assembly of oil-coated pieces
- Mechanical engineering
- Mounting & dismantling
- Mechanical Maintenance



## MATERIAL

- Polyester
- Seamless knit
- Stainless steel

## COATING

- Foam nitrile
- Nitrile



## NORMS



SHOWA

# S-TEX 377



## PACKAGING

- 10 Pair per polybag
- 12 Polybags per case
- 120 Pair per case



## SIZES

- S
- M
- L
- XL
- XXL



## COLOUR

- grey/ blue coating & black palm



## [ YOU MIGHT ALSO BE INTERESTED IN

SHOWA  
**376R**



**MATERIAL**  
Nylon  
**COATING**  
Foam nitrile  
**CATEGORY**  
General Purpose

SHOWA  
**377**



**MATERIAL**  
Nylon  
**COATING**  
Foam nitrile  
**CATEGORY**  
General Purpose

SHOWA  
**379**



**MATERIAL**  
Cotton  
**COATING**  
Foam nitrile  
**CATEGORY**  
Chemical

SHOWA  
**477**



**MATERIAL**  
Fixed insulated acrylic  
**COATING**  
Foam nitrile  
**CATEGORY**  
Cold

## [ USER INSTRUCTIONS

Do not use where there are chemical, electrical, thermal or entanglement risks. Wash at 40°C max. Performance levels as per standard EN388 retained after 3 washes, subject to variations linked to actual usage conditions. The performance levels apply to the coated surface only. Store in a dry place, away from the light.

## [ DISCLAIMER

The descriptions, characteristics, applications and photos are given for information purposes and do not constitute a contractual commitment. The manufacturer reserves the right to make any modifications it deems necessary.

## Get in touch

SHOWA International | WTC - Tower I - Strawinskyaan 1817 - 1077 XX Amsterdam - The Netherlands  
showagroup.eu | info@showagroup.eu

© SHOWA Group 2018 | All rights reserved